

# 2013 Product Design Higher

# **Finalised Marking Instructions**

#### © Scottish Qualifications Authority 2013

The information in this publication may be reproduced to support SQA qualifications only on a non-commercial basis. If it is to be used for any other purposes written permission must be obtained from SQA's NQ Assessment team.

Where the publication includes materials from sources other than SQA (secondary copyright), this material should only be reproduced for the purposes of examination or assessment. If it needs to be reproduced for any other purpose it is the centre's responsibility to obtain the necessary copyright clearance. SQA's NQ Assessment team may be able to direct you to the secondary sources.

These Marking Instructions have been prepared by Examination Teams for use by SQA Appointed Markers when marking External Course Assessments. This publication must not be reproduced for commercial or trade purposes.

#### Part One: General Marking Principles for PRODUCT DESIGN HIGHER

This information is provided to help you understand the general principles you must apply when marking candidate responses to questions in this Paper. These principles must be read in conjunction with the specific Marking Instructions for each question.

- (a) Marks for each candidate response must <u>always</u> be assigned in line with these general marking principles and the specific Marking Instructions for the relevant question. If a specific candidate response does not seem to be covered by either the principles or detailed Marking Instructions, and you are uncertain how to assess it, you must seek guidance from your Team Leader/Principal Assessor.
- (b) Marking should always be positive ie, marks should be awarded for what is correct and not deducted for errors or omissions.

#### GENERAL MARKING ADVICE: PRODUCT DESIGN HIGHER

The marking schemes are written to assist in determining the "minimal acceptable answer" rather than listing every possible correct and incorrect answer. The following notes are offered to support Markers in making judgements on candidates' evidence, and apply to marking both end of unit assessments and course assessments.

## Part Two: Marking Instructions for each Question

## **SECTION A**

Question	Expected Answer/s	Max Mark	Additional Guidance
1 a	The Lawnmower must:      cut grass     adjustable height of cut     be easily stored when not in use     be easily manoeuvred     be manufactured from durable materials that are suitable and appropriate for their function     be priced to suit the intended target market     ensure aesthetics suit the market niche or consumer aspirations     be used in larger gardens (lawnmower B)     cut on sloping ground (lawnmower A)     production costs significantly less than selling price.     looks obvious to use     be easy to empty (lawnmower B)     pick up cut grass (lawnmower B)     pick up cut grass (lawnmower B)     be easy to clean/maintain     safety (when in context) eg blades guarded     reference to suitable cable length (lawnmower A)     comply with relevant safety regulations     any other suitable statement.  Any 6  Comments Accept  Lifespan Corrosion issues Portability Comfortable to use Weather conditions Sustainability Circuit breaker (RCD)	6	No direct lift from stem.  NB – Lawnmower A has no grass catcher

Q	Question		Expected Answer/s	Max Mark	Additional Guidance
1	b		Statements which justify issues such as:  durability of material/impact resistance (non corrosion) *[Do not accept metal alloy]  strength to weight issues readily available materials  Nylon – self lubricating gears  HSS/tool steel – hardness rubber – excellent grip chemical resistance comfort of foam foam gives excellent grip suitability for production methods function of component parts aesthetic properties ease of cleaning re-cycling any other suitable statement	6	

Q	Question		Expected Answer/s	Max Mark	Additional Guidance
1	b		(cont)		
			Sample answers Aluminium offers an excellent strength to weight ratio which is ideal for use with lawnmower B as it has to be transported by the user. (1)  The nylon mesh offers an extremely light and hard wearing material that can be easily cleaned. (2)  PP is a good choice of material for lawnmower A as it is durable, easily maintained and offers a good strength to weight ratio. (3)  Metal alloy is durable (not acceptable/properties are not known. (0)  NB – mention of mass production can be awarded in (1b) only six valid statements @ 1 mark each (5+1)		

Que	estion	Expected Answer/s	Max Mark	Additional Guidance
1 (	c	Suitable Processes  Lawnmower A – Extrusion, Bending, Injection Moulding, Piercing & Blanking, Plastic/Powder/ Dip coating, Sharpening  Lawnmower B – Injection moulding, Compression Moulding, Welding, CNC Machining, Bending/press forming, Extrusion, Pressure die casting, sharpening, spray painting.	6	
		<ul> <li>Accept general term spray painting</li> <li>How manufacturing/assembly techniques are influenced by volume of production</li> <li>Process is suitable for the material eg (sheet metal for press forming)</li> <li>Statements could include:         Standardisation of sizes, component parts all the same size. No further finishing required. Shapes suitable for process.         Standardisation of components and materials chosen because they are easily sourced/formed.         Suitable for mass/batch production – injection moulding.         Economy of scale – mass/continuous production/JIT     </li> <li>Maximum of 3 for identification of process.</li> <li>(1 each process)</li> <li>Maximum of 3 marks per process</li> <li>(1 identification, 2 justification)</li> </ul> Comments Accept <ul> <li>Manufacture – Quality of standard components</li> <li>Consumer – High quality finish</li> </ul>		

Question		tion	Expected Answer/s	Max Mark	Additional Guidance
1	d		Any four issues explained in the context of ergonomics:	4	Bullet points which are not expanded to show understanding are not accepted.
			<ul> <li>Examples from:</li> <li>Anthropometrics relating to handle grip, position and locking</li> <li>Position of handles for operation (dead man's switch)</li> <li>Handle adjustment (Height)</li> <li>Hand size (for access to components)</li> <li>Finger traps</li> <li>Surface texture to prevent slipping</li> <li>Weight for lifting/strength issues</li> <li>Strain/fatigue issues</li> <li>Psychological issues – colour, ease of assembly, looks safe and easy to use</li> <li>Comfort during use</li> <li>Access for cleaning/maintenance</li> <li>Any other relevant answer.</li> <li>4 statements at 1 mark each</li> <li>1 mark can be awarded if range of issues are identified but not explained.</li> </ul>		

Question		on	Expected Answer/s	Max Mark	Additional Guidance
1	e		Any description from: Cost (only if compared) Aesthetics Durability Brand name/Image Recycling Easy to use/store Lightweight Grass catcher (Lawnmower B) Safety No need of electricity (Lawnmower B) Easy to move due to wheels (Lawnmower B) Iower disposable income (Lawnmower A) No cable, so it can be used more than 20m from a power point (Lawnmower B) Can be used on severe slopes (Lawnmower A) Any other acceptable answer.  4 issues described at 1 mark each (3+1) Comments Accept	4	

Q	Question		Expected Answer/s	Max Mark	Additional Guidance
1	f		NB – a maximum of 3 marks from any functional aspect. Any four identified issues described:  • Fitness for its purpose (not simply cut grass) • Durability to withstand continual use/outdoor environment • Safety aspects of function – dead man's trigger; electrical safety • Maintenance issues • Ease of use • Easy to clean • Ease of adjustment • Choice of materials (relating to function) • Stability of lawnmower • Portability • Storage • Any other acceptable issues.  Four issues identified, 4 issues at 1 mark each (3+1)	4	
				30	

## **SECTION B**

Q	Question		Expected Answer/s	Max Mark	Additional Guidance
2	а		<ul> <li>The benefits of drop forging are:</li> <li>Stronger than similar cast or machined products/improved strength characteristics</li> <li>Repeatable process</li> <li>Accuracy</li> <li>Complex shape</li> <li>Good surface detail</li> <li>One piece construction</li> <li>Or any other suitable answer.</li> </ul> 1 mark for explanation	1	
2	b		<ul> <li>The features of drop forging are:</li> <li>Parting lines/flashing/flash removal/split lines</li> <li>Quality of surface detail/texture</li> <li>One piece construction</li> <li>Contrast of finishes</li> <li>Evidence of further finishing might be apparent</li> <li>Draft angle/relief profile</li> <li>Or any other suitable answer.</li> </ul> No repetition from A <ul> <li>mark for each appropriate statement (2@1 mark)</li> </ul>	2	

Q	Question		Expected Answer/s	Max Mark	Additional Guidance
2	С		While most metals can be dropped forged, the material selected should be appropriate to the product.  Chromium alloy steel (Accept stainless steel) High carbon steel (Do not accept steel) Nickel/Nickel alloys Titanium  Reason for choice: Durability Toughness Resistant to corrosion (Chromium alloy steel, stainless steel, Nickel/Nickel alloys, Titanium) Any other suitable answer.  mark for suitable material mark for appropriate reason – one mark can be awarded for stating incorrect material but correct reason (applicable to given material)	2	
				5	

Q	uestion	Expected Answer/s	Max Mark	Additional Guidance
3		Description should include at least two aspects from:  Aesthetics to enhance function  Aesthetics to promote/enhance style  Shape/Layout of buttons enhanced by aesthetic  Form of product  Colour contrasts/harmonies  Contrast/harmonies in shapes  Gloss surface compared with matt surface  Texture  Any other suitable answer.  4 @ one mark for each appropriate description.  Maximum 2 marks per aspect.	4	Use of standard symbols - no marks
			4	

C	uestio	Expected Answer/s	Max Mark	Additional Guidance
4	а	<ul> <li>Any 2 issues explained with reference to the product</li> <li>Focussing product to specific target group</li> <li>Aspirational group – prestige, brand awareness</li> <li>Financial aspects</li> <li>Profitable segment of a market</li> <li>Satisfying specific market needs</li> <li>Any other relevant answer.</li> </ul> Generic description of market niche – one mark	2	

C	uestion	Expected Answer/s	Max Mark	Additional Guidance
4	b	<ul> <li>Any two issues described</li> <li>Fewer types of materials per product</li> <li>Lower volume of materials per product</li> <li>Materials that are easy to recycle/renewable</li> <li>Materials easily identifiable</li> <li>use alternative materials</li> <li>Product easily dismantled for recycling</li> <li>Any other relevant answer.</li> </ul>	2	
		Any 2		
4	c	<ul> <li>Any two issues described</li> <li>Demand for product</li> <li>Price point (Usually towards top end of market for batch produced items)</li> <li>Flexibility of design (batch)</li> <li>Flexibility of production</li> <li>Less machinery required but generally multipurpose machines to allow retooling (batch)</li> <li>Particular components which must be batch produced</li> <li>Standard components</li> <li>Production planning</li> <li>Production costs</li> <li>Any other relevant answer.</li> </ul> 2 marks can be awarded for a full description of an issue explaining reasons for production method.	2	
			6	

Q	uesti	on	Expected Answer/s		Max Mark	Additional Guidance
5	а	Developm Outsourci Ensure re Efficient p Reduce th Reduce to Efficient C Higher sta	ng to specialists liable delivery of raw materi roduction and process sche ne number of processes em	als duling oloyed es s	2	
				Any 2		
5	b	Reasons for of Although the profits  Longer are Less negales Sales states as Sales lasted Tablet 2 in the Although the profits and the profits are the profits and the profits are the profits and the profits are the profits are the profits and the profits are the profits	the sales are lower in terms are higher (from graph) and costlier lead time for Table ative profit during lead in for trearlier (Tablet 2) a longer (Tablet 2) an profit longer.	et 1 Tablet 2	3	
5	С	<ul> <li>Special of</li> <li>Increased</li> <li>Updated</li> <li>Introduce</li> </ul>	rice of product ifers (eg Free tablet case) I advertising versions (software) special editions/additional for	eatures Any 2	2	
				Ally 2		
					7	

Question	Expected Answer/s		Additional Guidance
6 a	<ul> <li>Cost of manufacture reduced (simple tooling)</li> <li>Speed and simplicity of assembly</li> <li>Can be purchased as standard components</li> <li>Unskilled labour can be employed</li> <li>Can be Flat-packed/Easily Stored/Easily Transported</li> <li>Fittings are produced to suit manufactured boards</li> <li>Standard components/parts</li> <li>Speed of manufacture is increased</li> <li>Any other relevant answer.</li> </ul> Any 2 explained	2	

Q	Question		Expected answer/s		Additional guidance
6	b		<ul> <li>Quality of finish</li> <li>Aesthetics</li> <li>Fashion/style</li> <li>Durability</li> <li>Strength issues</li> <li>Recyclability</li> <li>Any other relevant answer.</li> </ul>	2	
			Any 2 explained		
6	С		<ul> <li>Ease of recycling</li> <li>Changes in fashion/style</li> <li>Ability to change doors/worktops</li> <li>Durability of carcase materials and fittings</li> <li>Maintenance/replacement issues</li> <li>Obsolescence of appliances</li> <li>Any other relevant answer.</li> </ul>	2	
			Any 2 described		
				6	

G	Question		Expected Answer/s	Max Mark	Additional Guidance
7	а		All answers must <u>clearly</u> refer to simulation v user trials.  Explanation should include;	2	
			<ul> <li>Saving money on product development phase</li> <li>Reduced labour costs</li> <li>Money saved on testing components</li> <li>Quicker development phase</li> <li>Faster resetting time for tests</li> <li>Quicker feedback</li> <li>Exact conditions can be replicated</li> <li>Material wastage</li> <li>No human error</li> <li>Can run 24/7</li> <li>Safety aspects</li> </ul>		
			Or any other suitable answer.  Any 2		
7	b	i	Suitable materials;  Polycarbonate/ABS mix  ABS  Polycarbonate  SAN (Styrene Acrylonitrile Resin)  Or any other suitable material  [Do not accept thermoplastic alone as an answer]	1	

Q	Question		Expected Answer/s		Additional Guidance
7	b	ii	Advantages;  No material is lost  High strength  Cost effective  Component accuracy/detail  Reduced lead times  Assembled prototypes produced  Functional prototypes/products  Multiple materials can be used  Robust/tough  Impact resistance  Choice of colours  Or any other acceptable answer. [No repetition from 7 a)]  Disadvantages;  Can show "ribbing" from layers  High set up costs  Slow compared to other RP processes  Supports in structure might be needed  Large areas require longer build times  Or any other suitable answer.  One mark for each advantage and disadvantage.  (2 @ 1 mark)	2	
				5	

Q	Question		Expected Answer/s		Additional Guidance
8	а		<ul> <li>Observation</li> <li>Questionnaires/surveys</li> <li>User group testing</li> <li>Information from experts/focus groups</li> <li>Any other suitable description.</li> </ul>	1	
8	b		<ul> <li>Strength issues</li> <li>Fatigue</li> <li>Dexterity</li> <li>Mobility</li> <li>Any other suitable description.</li> <li>NB. Additional marks may be awarded for descriptions of <i>specific</i> physiological aspects.</li> </ul> Any 3	3	

Question		ion	Expected Answer/s		Additional Guidance
8	С		<ul> <li>Morphological Analysis</li> <li>Brainstorming</li> <li>Storyboard/mood board/image board</li> <li>Technology transfer</li> <li>Mind mapping/spider diagram</li> <li>Analysis of existing products</li> <li>Lateral thinking</li> <li>Any other suitable answer.</li> </ul>	2	
			Any 2		
8	d		<ul> <li>Use of programmes such as powerpoint</li> <li>Manual graphics</li> <li>Computer graphics</li> <li>Animation</li> <li>Modelling/prototyping</li> <li>Demonstration</li> <li>Any other suitable answer.</li> </ul> 1 mark for description of how presentation technique is used to explain concepts.	1	

[END OF MARKING INSTRUCTIONS]